

SB-DB-SBB-DBB a Sfera - A Saldare BW&SW SB-DB-SBB-DBB Ball Type - Welding BW&SW

Mod. 595-6 ... 895-6



Applicazioni

Intercettazione e sfiato di strumenti di pressione (manometri, pressostati, trasmettitori, ecc.).

Utilizzate per consentire un'installazione più compatta rispetto alle valvole tradizionali, particolarmente indicate in installazioni con presenza di vibrazioni.

Conessioni

A saldare BW o SW
Filettate secondo ANSI-ASME B1.20.1
ISO 228 - ISO 7/1

Rating

Secondo schedula

Tenute (std: T -46 ÷ +200 °C)

Sfera: Peek
Bonnet: Grafite (standard)

Peculiarità

Otturatore del bonnet svincolato dallo stelo
Spina di blocco del bonnet
Protezione antipolvere
Riduzione di tempi e costi d'installazione

Applications

Pressure instruments isolation and vent (gauges, switches, transmitters, etc.).

Used as alternative to conventional manifold to permit a more compact installation, particularly recommended in presence of vibration.

Connections

Welding BW or SW
Threaded to ANSI-ASME B1.20.1
ISO 228 - ISO 7/1

Rating

To schedule rating

Seals (std: T -46 ÷ +200 °C)

Ball: Peek
Bonnet: Graphite (standard)

Features

Bonnet with non rotating trim
Bonnet locking pin
Dust protection
Reduction of time and installation cost

Ingresso Inlet	Uscita Outlet	Dimensioni Dimensions		Peso Weight
		A (mm)		
BW / SW	NPT - F	SB / SBB	DB / DBB	Kg
1/2"	1/2" std	228	280	6,5
3/4"	1/2" std	228	280	6,5
1"	1/2" std	228	280	6,5

Come ordinare Ordering Information

Versione a sfera Ball Type

SB	59	Single Block
DB	69	Double Block
SBB	79	Single Block&Bleed
DBB	89	Double Block&Bleed

Connessioni IN Connections IN

D	1/2"
E	3/4"
F	1"
X	A richiesta / On demand

*Sfiato / Vent (solo per / only for SBB-DBB)

B	1/4" NPT-F
D	1/2" NPT-F (std)

Materiale Tenuta Seal material

PG	Peek / Graphite (std)
X	A richiesta / On demand

Opzioni / Options Vedere tabella / See table

DBB - 89 5 - BW40 D D D - L - PG - * * *

* NPT standard
Aggiungere / Add:
R = BSPT thread
G = BSPP thread
Es / Ex: DR = 1/2" BSPT

Scheda / Schedule

BW 40
BW 80
BW 160
BW XXS
SW 40
SW 80
SW 160
SW XXS

* Connessioni OUT Connections OUT

D	1/2" (std)
E	3/4"
F	1"

Materiali / Materials

L	S.S. 316L
DL	S.S. 316 / 316L (Dual grade)
N	S.S. 316 Nace
C	C.S. A 105
LF2	C.S. A 350 LF2
D	Duplex F51
SD	Superduplex
M	Monel 400
X	A richiesta / On demand

Connessioni / Connections

5	BWxFiletto F / BWxThread F
6	SWxFiletto F / SWxThread F

